

Truck Loading Conditions



	SH 10 Dump Truck ¹⁾	SH 20/SO 143 Silo Truck ²⁾	Packed goods Tautliner Truck ³⁾	Packed goods Container ⁴⁾
Registration Time Mo-Fr 06:45 - 16:00	X	X	X	X
Washed with cleaning certificate		X		
Rust-free	X	X		
Clean swept	X		X	X
Without foreign smell	X	X	X	X
Lying tank	No, only after authorisation by customer			
Tension belts/Non-slip mats (L: 30x15x0.4 cm / Friction value 0.8 my)			X	
Tarpaulin	X		X	
Steel floor			NO	NO
Maximum overall weight	40.5 to	40.5 to	40.0 to	Depending on nameplate and truck load capacity

²⁾ Visual control of bulk trucks before loading.

¹⁾ Control of cleanliness including taking pictures of the load floor (dump trucks).

³⁾ Load securing full truck (19-23 pallets): 16 tension belts + 30 non-slip mats

³⁾ Load securing part load (less than 19 pallets): 2 tension belts + 4 non-slip mats per pallet

⁴⁾ Containers must not be dented and/or leaky.

⁴⁾ The floor must be continuous so that pallets can be moved.

⁴⁾ In the inside no salient parts which could damage the cargo.

